



# 10.4" LCD Industrial Flat Panel Monitor

IPM-10

## Features

- 10.4" SVGA TFT LCD Panel support 800 × 600 pixels
- 6mm Aluminum front bezel with strengthen glass
- Rugged construction and slim modularized design
- Input signal : VGA + DVI + AUDIO
- 230 cd/m2 brightness
- OSD control keys to optimize the display
- AC 100-240V wide range external ac adapter
- Panel ( Flush ) mount with bracket
- NEMA4 / IP 65 compliant front panel
- Meet standard VESA hole ( 75x75 mm ), support desk top stand / wall mount/ swing arm mounting

## Design Drawings



## Specifications

### TFT characteristics

Display Type : 10.4" SVGA TFT LCD  
Resolution : 800 × 600  
Max.color : 16.2M  
Luminance : 230 cd/m2  
View Angle : 120° (H) , 100° (V)  
Pixel Pitch : 0.264 x 0.264 mm  
Contrast Ratio : 500 : 1  
Response Time : 35 ms  
LCD MTBF : 50,000hrs

### Mechanical and Environmental

Construction : Heavy duty steel and aluminum front panel  
Dimensions (WxHxD) : 305 x 220 x 36 mm  
Weight : Net: 3.5kg , Gross:5.0 kg  
Operating temperature : 0 °C to 50 °C  
Storage temperature : -20 °C to 60 °C  
Storage humidity : 10% to 90% non-condensing  
Anti-Vibration : 17HZ-500 HZ 1G PTP  
Anti-Shock : 1G / peak( 11m sec)

### Available Options

Touch Screen : Resistive Type with USB and RS232 controller  
DC Power Input : wide Range 8~30v DC input  
AV input : Composite video/audio, S-video input

### Power Specifications

Input: 100~240VAC,50/60Hz  
Output: DC12V@ 5A / 60W ,external ac adapter

### Input Signals

RGB Signal : D-SUB 15P Connector (female)  
DC input : DC Jack (2.1mm)  
Video input (option) : RCA Connector  
S-Video signal (option) : S-Video (SVHS)plug  
DVI-D Signal : DVI-D input 24pin connector (female)  
Touch screen RS232 (option) : D-SUB 9p connector (female)  
Touch screen USB (option) : USB-A type connector (female)

# 10.4" LCD Industrial Flat Panel Monitor

IPM-10

## Certification and Approvals

• CE/FCC/ROHS

## Ordering Information

### VGA + DVI input


- IPM-10 : 10.4" Industrial Flat Panel Monitor with VGA + DVI + Audio input  
IPM-10T/C : 10.4" Industrial Flat Panel Monitor with VGA + DVI + Audio input, with touch screen and RS232 controller  
IPM-10T/U : 10.4" Industrial Flat Panel Monitor with VGA + DVI + Audio input, with touch screen and USB controller

### AV input

- IPM-10A : 10.4" Industrial Flat Panel Monitor with VGA + DVI + Audio + S-Video + Video input or BNC input  
IPM-10AT/C : 10.4" Industrial Flat Panel Monitor with VGA + DVI + Audio + S-Video + Video input or BNC input, with touch screen and RS232 controller  
IPM-10AT/U : 10.4" Industrial Flat Panel Monitor with VGA + DVI + Audio + S-Video + Video input or BNC input, with touch screen and USB controller  
DC-DC Power : DC 8 ~ 30v input power module

## Design Drawings

Unit : mm



All specifications are subject to change without prior notice